CODE QUIZ

April 2026

1. Per the 2025 California Residential Code, Section R322.3, where care facilities are permitted to be constructed and serve five or fewer persons receiving medical or custodial care or persons of any age receiving day care, within a dwelling unit as permitted per Section R101.2, the portions of the dwelling used to operate a business providing care shall be accessible in accordance with Chapter 11B of the California Building Code.
    a. True
    b. False

2. Per the 2025 California Building Code, Section 202 Definitions, an assemblage of specific materials or products that are designed to resist the passage of fire through voids created at the intersection of fire barriers and the underside of roof assemblies that are not fire-resistance rated for a prescribed period of time is _____.
    a. fire barrier ceiling interface system
    b. fire diaphragm boundary
    c. continuity head-of-wall system
    d. wall ceiling firestop

3. Per 2025 California Wildland-Urban Interface Code, Section 501.1, buildings and structures in a wildland-urban interface area shall be constructed in accordance with the California Building Code and this code, except for:
    a. Group U accessory structures not exceeding 120 square feet in floor area located not less than 50 feet from applicable buildings.
    b. Additions to and remodels of buildings originally constructed prior to July 1, 2008
    c. New accessory buildings, miscellaneous structures
    d. a only
    e. a, b & c

4. Per 2025 California Electrical Code, Section 210.52(C)(2), receptacle outlets, if installed to serve an island or peninsular countertop or work surface, shall be installed in all areas except for:
    a. on or above, but not more than 20” above, a countertop or work surface
    b. in a countertop using receptacle outlet assemblies listed for use in countertops
    c. in a work surface using receptacle outlet assemblies listed for use in work surfaces or listed for use in countertops
    d. below countertop or work surfaces not more than 12” below the countertop or work surface.

5. Per 2025 California Building Code, Section 11B-224.1.2, in transient lodging facilities (hotels/motels), bathroom doors shall be either sliding or hung to swing _____.
    a. inward into the bathroom
    b. in the direction of egress from the bathroom
    c. either a or b is acceptable